

Remote Paging Microphone



CRM-RPM12

Remote Paging Microphone

Upto 32 paging microphone | 12 Programmable keys | Live paging

| Fully real time monitored | EN 54 Compliance

Remote paging Microphone for remote control of the CRM-500Z6 and CRM-500Z8 controllers. The remote microphone is designed with 12 zone buttons with busy & working indicators. One or multiple external 12 zone expansion keypad CRM-12K could be cascaded together for up to 120 zone operation. Distance to the controller up to 600 m, with the possibility of redundant connection. It has volume adjustment, external mic / line input, possibility of PTT (push-to-talk) operation.



Key Features

- 12 Zone remote paging station
- Up to 120 zones by cascaded the zone keypad CRM-12K
- Support 32 remote microphones of loop redundancy connection
- remote microphone unit is fully real time monitored
- Support PTT and lock type two modes
- CAT-6 cable up to 600 meters
- Support 24V phantom power

Technical Specifications

Power Supply	Phantom 20 ~ 27.5 V
Power Consumption	3W
Zone Capacity	12
Communication distance	600m
Line Inputs	350mV, 10k Ω
Mic Input	5mV, 600 Ω
Frequency Response	80Hz~16kHz
THD	<1% at RMS,1KHz
Signal to Noise Ratio	>70dB
Humidity	<95% no condensation
Dimension (WxHxD)	153×52×195 mm
Weight	0.9kg

Products are continually improved. All specifications are subject to change without prior notice | V1.1 | 04062024 | For more information, contact techsupport@tsgaudioinnovation.com