

Remote Paging Microphone



TSG-RPM

Remote Paging Microphone for Mixer Amplifier

Upto 06 microphone | 6 Zones selection keys | Live announcement

Microphone desk with keys for zone selection, general call and for paging. It has volume control and external audio input that replaces the microphone built into the 40 cm gooseneck. A maximum of 06 units can be connected to the TSG-120MA/TSG-240MA/TSG-500MA mixer amplifier via cat6 FTP cable and RJ45 connectors, at a distance of up to 300 meters



Key Features

- **6 Zone remote paging station**
- **All zones selection button**
- **Support 6 remote microphones per mixer amplifier**
- **Power, send and busy indicators**
- **Microphone is directly powered by the mixer amplifier**
- **Microphone with volume control and aux input**
- **Communication up to 300 meters – CAT6 cable**

Technical Specifications

Power Supply	Direct from the amplifier, 24V DC, $\pm 20\%$
Power Consumption	3W
Zone Capacity	6
System Capacity	6 Remote microphones
Communication distance	300m
Line Inputs	350mV, 10k Ω
Mic Input	5mV, 600 Ω
Frequency Response	80Hz~16kHz
THD	<1% at RMS, 1KHz
Signal to Noise Ratio	>70dB
Humidity	<95% no condensation
Dimension (WxHxD)	175×52×150mm
Weight	0.8kg

Products are continually improved. All specifications are subject to change without prior notice | V1.1 | 04062024 | For more information, contact techsupport@tsgaudioinnovation.com